

NAVMAN **8120**

It's the sleek 12-inch navigation console that's designed for the modern boating experience.

The 8120 is the low-profile, low power multifunction marine computer or datahelm every fisherman, cruiser and sailor is calling for, integrating GPS, sonar, fuel management and video functionality into a daylight viewable high-resolution screen.



Chart. Navman's 32 MB chart gets you started for global navigation, or install C-Map's NT MAX™ technology for detailed chart data, value-added port info and land detail.

Sonar. The 8120 is equipped with a powerful 1 kW (RMS) sounder that automatically adjusts the output power (1 kW or 600 W) to match the wattage of the transducer. No black box required, just plug the transducer of choice directly into the 8120 and you're up and running.

Fuel Management. With the NAVMAN 8120, you have on-demand access to your engine's performance data as well as SmartCraft™ management for Mercury engines.


<u>Video.</u> For the first time, Navman brings video to your helm. Hook a security camera up for live deck monitoring, engine room surveillance or underwater views. Or even run a DVD player or camcorder into the NAVMAN 8120 for infotainment[†].

† A separate audio output device required.

NAVMAN 8120 Features & Benefits

- ▲ Incredibly crisp, clear, vivid daylightview 12.1 " 800 x 600 pixel screen
- ▲ C-Map NT MAX[™] compatibility with built-in 32 MB chart
- ▲ The classic, easy-to-use Navman interface
- ▲ Radar compatibility (November 2006)
- ▲ GPS sensor included
- ▲ Up to 1 kW sonar no sounder module required
- ▲ Video input
- Flexible fuel management options: Gasoline and Mercury SmartCraft™ *
- ▲ 2-year warranty
- * Requires optional fuel kit / SmartCraft™ gateway

NAVMAN 8120



NAVMAN 8120 SPECIFICATIONS

Physical Attributes			
Daylight viewable TFT color screen (pixels)	800 x 600		
Screen size (diagonal)	12.1 " (304 mm)		
Supply voltage	12 - 24 V		
Waterproof rating	IPx6, IPx7		
Mounting	Flush or bracket		
Video			
Video Input	BNC (PAL / NTSC)		
Chart / GPS Navigation			
Embedded world map	32 MB		
Waypoint memory	3000		
Routes	25 - up to 50 waypoints / route		
Tracklogs (time or distance)	5:1 x 2000 points, 4 x 500 points		
C-Map Cartography (on SD card)	NT MAX		
C-Map SD card slots	2		
C-Map user card support	Yes, on SD cards		
Sonar			
Transmit frequency	50 200 kHz		
Output power (RMS)	600 1000 W		
Depth range	2 — 3300 ft		
	(0.6 — 1000 m)		

Note: Although the 8120 is a multifunction product, the sonar transducer will be sold separately due to the weight of the 1 kW transducers and the number of options now

The 8120 detects if the transducer requires 600 W or 1 kW of power and supplies it accordingly.

Fuel Management *			
Instant fuel flow Fuel Used / Remaining Economy Range	Gasoline & Diesel		
SmartCraft™ capable	Yes		
Communications			
VHF DSC Interface	Yes		
NMEA 0183 (ver. 2) input	Standard input from GPS or DGPS receiver, BWR, DBT, DPT, GGA, GLL, GSA, GSV, HDG, HDM, HDT, MTW, MWV, RMC, VHW and VTG		
NMEA 0183 (ver. 2) output	APA, APB, BWR, DBT, DPT, GGA, GLL, GSA, GSV, MTW, RMB, RMC, VHW, VLW, VTG, XDR and XTE		
Fish Forecast / Weather Station **	Yes		
Track-Your-Buddy **	Yes		

Requires optional fuel kit / SmartCraft™ gateway

** Requires Navman VHF 7200 radio to use this feature.

	NAVMAN 8120 Part Numbers		
9	Head unit only	AA006620R	
	- with GPS antenna	AA006624R	



HEADQUARTERS

Navman NZ Limited 7-21 Kawana St. Northcote. P.O. Box 68 155 Newton, Auckland, New Zealand. Ph: +64 9 481 0500 Fax: +64 9 481 0590

e-mail: marine.sales@navman.com Website: www.navman.com

USA

Brunswick New Technologies Marine Electronics 30 Sudbury Road, Acton MA 01720 Ph: +1 866 628 6261

Ph: +1 866 628 6261 Fax: +1 978 897 8264

e-mail: sales@bntmarine.com

AUSTRALIA

Navman Australia Pty Ltd Suite 2, 408 Victoria Road Gladesville, NSW 2111 Australia Ph: +61 2 9879 9000

Fax: +61 2 9879 9001

e-mail: sales@navman.com.au

EUROPE

PLASTIMO INTERNATIONAL 15, rue Ingénieur Verrière BP435 56325 Lorient Cedex Ph: +33 2 97 87 36 36 Fax: +33 2 97 87 36 49 e-mail: plastimo@plastimo.fr

e-mail: plastimo@plastimo.f Website: www.plastimo.fr